

# Instruction

## HDMI Splitter Mini

Model No:HDSPM0102S

HDSPM0104S

### Dear customer

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting this product. Please keep this manual for future reference.

### FEATURES

- **HDSPM0102S** :one HDMI input signal split to 2 HDMI sink devices
- **HDSPM0104S** :one HDMI input signal split to 4 HDMI sink devices
- HDCP protocol compliant
- Support deep color 36bit, Support Blue-Ray 24fs/HD-DVD/xvYCC
- Digital audio format, as DTS-HD/Dolby-trueHD/LPCM7.1/DSD
- Support signal retiming
- Support input up to 20metre AWG24 HDMI standard cable length, output up to 15metre AWG24 cable length
- Need DC5V power supply

Power adapter supply ..... DC: 5V  
Power adapter format ..... Input: AC (50HZ, 60HZ) 100V-240V; Output: DC5V  
Operating Temperature range.....(-15 to +55°C)  
Operating Humidity range..... to 90%RH (No Condensation)  
Dimension (L x W x H) ...**124X52X20mm/198.5X67X21mm**  
Weight..... **240g/405g**

### WARNING

#### TO REDUCE THE RISK OF FIRE,ELECTRIC SHOCK OR PRODUCT DAMAGE:

- 1.Do not expose this apparatus to rain, moisture, dripping or splashing and make sure that no object filled with liquids, such as vases, are placed on the apparatus.
- 2.Do not install or place this unit in a bookcase, built-in cabinet or in a confined space. Ensure the unit is well ventilated.

### CONNECTING AND OPERATING

- 1.Connect the HDMI cable from the HDMI devices into HDMI splitter inputs.
- 2.Connect the HDMI cable from your display (monitor or projector) into the HDMI splitter outputs.

### SPECIFICATIONS:

#### HDSPM0102/04S

HDMI resolution..... **4kx2k**, 1080p24fs,1080p,1080i,720p,576p,576i,480p,480i  
Support video color format .....24bit/deep color 36bit  
Support audio format ..... DTS-HD,Dolby-trueHD,LPCM7.1,DSD  
Max transmission bandwidth .....10.2Gbps  
Input TMDS signal.....0.5~1.5Volts p-p  
Input DDS signal.....5Volts p-p(TTL)  
Input cable distance .....<20m HDMI AWG24  
Output cable distance ..... 15m AWG24 HDMI standard cable  
Max working current ..... 900/1300 mA

- 3.To prevent the risk of electric shock or fire hazard due to overheating, do not obstruct the unit's ventilation openings with newspapers, tablecloths, curtains, and similar items.
- 4.Do not place near any heat sources such as radiators, heat registers, stoves and etc.
- 5.Do not place the units on the sources of naked flames, such as lighted candles, and so on.
- 6.Clean this apparatus only with dry cloth.
- 7.Unplug this apparatus during lightning storms and unused for long time.
- 8.Protect the power cord from being walked or pinched, particularly at the plugs.
- 9.Only use attachments/accessories specified by the manufacturer.
10. Refer all servicing to qualified service personnel.